

DESCRIPTION

| | | | |
|-------------------|--------------------------|------------------|----------|
| Total Thickness | EN ISO24346 (EN 428) | mm | 2 |
| Weight | EN ISO 23997 (EN 430) | g/m ² | 2000 |
| Width | EN ISO 24341 (EN 426) | cm | 100 |
| Length | EN ISO 24341 (EN 426) | m | 7.5 |
| Packaging content | | m ² | 7.5 |
| Packaging Weight | | kg | 15 |
| Article code | | | 16980001 |

CLASSIFICATION

| | | | |
|-------------|------------|-------|---|
| Fire rating | EN 13501-1 | class | Cfl-s1 (underlayer alone) Bfl-s1 (with Creation 55 / Creation 40 / Creation 30 / Virtuo 55 / Virtuo 30) |
|-------------|------------|-------|---|

PERFORMANCE

| | | | |
|-------------------------|---------------------|--------------------|--------|
| Impact sound insulation | EN ISO 717-2 | dB | 16 |
| Thermal resistance | EN 12664 | m ² K/W | 0.01 |
| Compressive Strength | EN ISO 3386 / EN826 | kPa | > 450 |
| Compressive Strength | EN ISO 3386 / EN826 | t/m ² | > 45 |
| Punctual Conformability | CEN/TS 16354 | mm | ~ 0.79 |



This product is recommended by Gerflor for the following products :

- CREATION 55
- CREATION 40
- CREATION 30
- VIRTUO 55 (For classe 22 use only)
- VIRTUO 30 (For classe 22 use only)